

TECHNICAL DATA – 1 of 1

EzyForm F17

Formwork

TECHNICAL PROPERTIES

Sizes Available	2440 x 1220 18mm, 11 plies
Structural Rating	Non-Structural
Edge Seal	Waterproof paint
Environmental	Legally sourced plantation wood, FSC
Film Colour	Dark Brown, Black and Brown
Stress Grade	F17
Film Density	Black on 2 Faces 40/135GSM
Density	±559kg/m ³
Timber Species	Acacia or Eucalyptus
Moisture Content	< 12%
Tolerances	As per AS/NZS 2369
Adhesives	Phenolic Glue, Type A Bond
Off-form Finish	Class 2 (1st pour, single use) and class 3
Glue Bond	Exterior, WBP, MUF (Melamine Urea Formaldehyde)
Emissions	E1
Number of Cycles	> 12 (if applied, handled and maintained correctly)
Hardness	5900-6800 MPA

HANDLING AND STORAGE

Boards can be cleaned with warm water after use to remove any remaining material adhered to the surface. They must be stored on a hard, flat surface, avoiding direct contact with the ground and in a dry environment protected from water. Sudden changes in these conditions can affect the properties of the board. Separate the boxes from each other with clean, dry and resistant spacers of uniform thickness, suitable for loading/unloading with forklift.